

AndonWIRELESS / Andon product

WeAssist/AndonWireless Transceiver921MHz



Part No.: 862.000.05



MECHANICAL DATA

| | |
|-----------------------------|-------|
| Height | 66 mm |
| Diameter | 70 mm |
| Materials | PC |
| Housing colour | Black |
| Protection category | IP65 |
| Connection | USB |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| Weight with packaging | 89 g |
| Product weight | 68 g |

ELECTRICAL DATA

| | |
|---------------------------|--------------------|
| Operating voltage | 24V |
| Operating voltage type | DC |
| Rated operational current | 60 mA |
| Protection class | Protection class 3 |
| Pollution degree | 3 |
| Radio frequency min/max | 921.000 MHz |
| Radio channels | 6 |

APPROVAL DATA

| | |
|------------------------------|--------------------------------|
| Conforms with CE | No |
| Conforms with RoHS directive | Fulfills substance restriction |
| WEEE | Yes |
| Conforms with CCC | No |
| Conforms with UL | cULus |
| Conforms with FCC | Yes |
| Conforms with IC | Yes |
| EAC certificate available | No |
| Conforms with AS-I | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |
| Conforms with VdS | No |



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

AndonWIRELESS / Andon product

WeAssist/AndonWireless Transceiver921MHz

DRAWING



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.